

#10 WOODTITE HLX FASTENERS

HEAD

- Head Style: ¼"
- Wet paint application for consistent socket fit and weathering performance

WASHER

- Bonded Seal Washer

THREAD

- Major Hi Diameter: .200"/.190"
- Major Low Diameter: .165"/.155"
- Minor Diameter: .133"/.128"
- Aster feature on 1st two full threads

POINT

- Type-17 Point helps to penetrate metal more quickly while minimizing chips
- 26 Degree Sharp Point for quick piercing

FINISH

- Zinc Plated with Oxyseal® Coating

MATERIAL

- Carbon Steel



#10 WOODTITE HLX

SIZE	ITEM#	# PER M	BOX QTY
10-14 x 1	82639ZBN99XXHSL	7.4	2,500
10-14 x 1-1/2	82642ZBN99XXHSL	9.8	2,500
10-14 x 2	82644ZBN99XXHSL	12.0	2,000
10-14 x 2-1/2	82646ZBN99XXHSL	14.2	1,500
10-14 x 3	82648ZBN99XXHSL	16.4	1,000

ENGINEERING TEST REPORT

Minimum Torsional	Minimum Tensile	Minimum Shear	Pull Out SPF2 – 1.5" Penetration	Revolutions/In.
68 in. lbs	2,100lbs.	1,265 lbs.	1,090 lbs.	7.0

All test results and recommendations are based on laboratory tests. Specific job site conditions should be taken into consideration when specifying the proper fastener. Actual field values may vary, therefore we assume no liability for use of this information. Pull out values are a measurement of wood material strength

#10 WOODTITE HLX HIGH-LOW FASTENER



Bonded seal washer
to provide for
positive sealing



Wet paint
application for
consistent socket
fit and weathering
performance



High Major Threads
with Low Minor
Threads for enhanced
pullout values

INSTALLATION INSTRUCTIONS:

- Do not use impact style guns
- Use an electric screw gun
2,500 RPM max

Type-17 Point helps
to penetrate metal
more quickly while
minimizing chips

Aster threads to cut
through hard woods
and knots

26 Degree Sharp Point



A Marmon/Berkshire
Hathaway Company

1628 Troy Road, Ashland, OH 44805
800-321-6977 • fax 419-289-2564

email: technical@atlasfasteners.com • website: www.atlasfasteners.com